SAFETY DATA SHEET



Chemask® (UFI)

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier	
Product name	: Chemask® (UFI)
Product code	: CM1, CM8
Product description	: Mask type: Coating.
Product type	: Liquid.
Other means of identification	: CM1, CM8 Mask type: Coating. Industrial/Professional use UFI: W9C8-D09D-J009-HQXH

1.2 Relevant identified uses of the substance or mixture and uses advised against

Not applicable.

1.3 Details of the supplier of the safety data sheet

Manufacturer Chemtronics 8125 Cobb Center Drive Kennesaw, GA 30152

Tel. 770-424-4888 or toll free 800-645-5244

Distributor

Importer ITW Contamination Control BV Saffierlaan 5 VZ-2132 Hoofddorp The Netherlands

Email: info@itw-cc.com

Tel: +31 88 1307 400 FAX: +31 88 1307 499 Website: www.Chemtronicseu.com

e-mail address of person responsible for this SDS	: Importer/Only Representative Bay 150 Shannon Industrial Estate Shannon County Clare Ireland V14 DF82 +353 61 771 500

National contact

Chemask® (UFI)

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

ITW Contamination Control BV Saffierlaan 5 VZ-2132 Hoofddorp The Netherlands

Email: info@itw-cc.com

Tel: +31 88 1307 400 FAX: +31 88 1307 499 Website: www.Chemtronicseu.com

1.4 Emergency telephone number

National advisory body/Pois	on Centre
Telephone number	: EMERGENCY HEALTH INFORMATION: Austria 01 406 43 43, Belgium +070 245 245, Bulgaria +359 2 9154 233, Croatia +3851 2348 342, Cyprus 1401, Czech Republic +420224 919 293, Denmark +45 8212 1212, Estonia 16662, Finland 0800 147 111, France +33 (0) 1 45 42 59 59, Germany +49-30-18412-0, Greece (0300) 2107793777, Hungary +36-80-201-199, Iceland 543-4071, Ireland 01 809 2566, Italy 0382-24444, Latvia +371 67042473, Lithuania +370 (85)2362052, Luxembourg +352 8002 5500, Netherland +31 88 75 585 61, Norway +47 22 59 13 00, Poland +48 42 2530 400, Portugal +351 800 250 250, Romania +40213183606, Slovakia +421 2 5477 4166, Slovenia 112, Spain +34 91 562 0420, Sweden 112 United Kingdom (England or Wales) 0845 46 47 or Scotland 08454 24 24 24 (UK only)
<u>Supplier</u>	
Telephone number	: Chemtronics Product Information: 800-TECH-401 (800-832-4401) Chemtronics Customer Service: 800-645-5244
Hours of operation	: 8:00 AM to 5:00 PM
Information limitations	: EMERGENCY HEALTH INFORMATION: EMERGENCY SPILL INFORMATION: Transport information

SECTION 2: Hazards identification

2.1 Classification of the subs	stance or mixture
Product definition	: Mixture
Classification according to	Regulation (EC) No. 1272/2008 [CLP/GHS]
Acute Tox. 3, H301	
Acute Tox. 3, H311	
Acute Tox. 3, H331	
Skin Sens. 1, H317 Aquatic Chronic 2, H411	
•	exercises according to Degulation (EC) 1979/2009 as amonded
I ne product is classified as n	azardous according to Regulation (EC) 1272/2008 as amended.
Ingredients of unknown toxicity	 98.5 percent of the mixture consists of component(s) of unknown acute oral toxicity 100 percent of the mixture consists of component(s) of unknown acute dermal toxicity
	100 percent of the mixture consists of component(s) of unknown acute inhalation toxicity
Ingredients of unknown ecotoxicity	: Contains 98.5% of components with unknown hazards to the aquatic environment
See Section 16 for the full tex	t of the H statements declared above.
See Section 11 for more data	iled information on booth offacts and summtand

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Chemask® (UFI)

SECTION 2: Hazards	ic	lentification
Hazard pictograms	:	
Signal word	:	Danger
Hazard statements	:	Toxic if swallowed, in contact with skin or if inhaled. May cause an allergic skin reaction. Toxic to aquatic life with long lasting effects.
Precautionary statements		
Prevention	:	Wear protective gloves and protective clothing. Avoid release to the environment. Avoid breathing vapour. Do not eat, drink or smoke when using this product. Wash thoroughly after handling.
Response	:	Collect spillage. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor. IF SWALLOWED: Immediately call a POISON CENTER or doctor. Take off immediately all contaminated clothing and wash it before reuse. IF ON SKIN: Call a POISON CENTER or doctor if you feel unwell. Wash with plenty of water. If skin irritation or rash occurs: Get medical advice or attention.
Storage	:	Not applicable.
Disposal	:	Dispose of contents and container in accordance with all local, regional, national and international regulations.
Hazardous ingredients	;	zinc bis(dibutyldithiocarbamate) methanol
Supplemental label elements	:	FOR INDUSTRIAL USE ONLY For professional use only.
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	:	Not applicable.
Special packaging requirem	en	<u>ts</u>
Containers to be fitted with child-resistant fastenings	:	Not applicable.
Tactile warning of danger	1	Not applicable.
2.3 Other hazards		
Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII	:	This mixture does not contain any substances that are assessed to be a PBT or a vPvB.
Other hazards which do not result in classification	:	None known.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

: Mixture

Chemask® (UFI)

SECTION 3: Composition/information on ingredients

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Туре
zinc bis (dibutyldithiocarbamate)	EC: 205-232-8 CAS: 136-23-2 Index: 006-081-00-9	≤5	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 STOT SE 3, H335 Aquatic Acute 1, H400 Aquatic Chronic 1, H410	M [Acute] = 1 M [Chronic] = 1	[1]
methanol	EC: 200-659-6 CAS: 67-56-1 Index: 603-001-00-X	<3	Flam. Liq. 2, H225 Acute Tox. 3, H301 Acute Tox. 3, H311 Acute Tox. 3, H331 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 1, H370	ATE [Oral] = 100 mg/kg ATE [Dermal] = 300 mg/kg ATE [Inhalation (vapours)] = 3 mg/l STOT SE 1, H370: $C \ge 10\%$ STOT SE 2, H371: $3\% \le C < 10\%$	[1] [2]
titanium dioxide	EC: 236-675-5 CAS: 13463-67-7 Index: 022-006-00-2	<1	Carc. 2, H351 (inhalation) Aquatic Chronic 2, H411	-	[1] [*]
ammonia	EC: 215-647-6 CAS: 1336-21-6 Index: 007-001-01-2	<1	Acute Tox. 4, H302 Skin Corr. 1B, H314 Eye Irrit. 2, H319 STOT SE 3, H335 Aquatic Acute 1, H400 Aquatic Chronic 3, H412	ATE [Oral] = 350 mg/kg STOT SE 3, H335: C ≥ 5% M [Acute] = 1	[1]
			See Section 16 for the full text of the H statements declared above.		

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

<u>Type</u>

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

[*] The classification as a carcinogen by inhalation applies only to mixtures placed on the market in powder form containing 1% or more of titanium dioxide particles with aerodynamic diameter \leq 10 µm not bound within a matrix.

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

- Eye contact
- : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.

Chemask® (UFI)

SECTION 4: First aid measures

Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Skin contact	: Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. If necessary, call a poison center or physician. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	: Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

Eye contact	: Adverse symptoms may include the following: irritation redness watering
Inhalation	: Adverse symptoms may include the following: headache dizziness/vertigo drowsiness/fatigue
Skin contact	: Adverse symptoms may include the following: irritation redness
Ingestion	 Adverse symptoms may include the following: Ingestion Seek medical attention.

Notes to physician	: In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Specific treatments	: No specific treatment.

Chemask® (UFI)

SECTION 5: Firefighting measures

5.1 Extinguishing media		
Suitable extinguishing media	:	Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	:	None known.
5.2 Special hazards arising f	ron	the substance or mixture
Hazards from the substance or mixture	:	In a fire or if heated, a pressure increase will occur and the container may burst. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Hazardous combustion products	:	Decomposition products may include the following materials: carbon dioxide carbon monoxide nitrogen oxides sulfur oxides metal oxide/oxides
5.3 Advice for firefighters		
Special protective actions for fire-fighters	:	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	:	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.
	4	

SECTION 6: Accidental release measures

6.1 Personal precautions, pro	ote	ctive equipment and emergency procedures
For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Do not breathe vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	:	If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
6.2 Environmental precautions	:	Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.
6.3 Methods and material for	со	ontainment and cleaning up
Small spill	:	Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	:	Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor.

Date of issue/Date of revision

Contaminated absorbent material may pose the same hazard as the spilt product.

Chemask® (UFI)

SECTION 6: Accidental release measures

- 6.4 Reference to other sections
- : See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not breathe vapour or mist. Do not ingest. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Seveso Directive - Reporting thresholds

Danger criteria

	Notification and MAPP threshold	Safety report threshold
H2	50 tonne	200 tonne
E2	200 tonne	500 tonne

7.3 Specific end use(s)

Recommendations

Not available.Not available.

Industrial sector specific solutions

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values		
	EU OEL (Europe, 10/2019). Absorbed through skin. Notes: list of indicative occupational exposure limit values TWA: 260 mg/m ³ 8 hours. TWA: 200 ppm 8 hours.		

Biological exposure indices

No exposure indices known.

Chemask® (UFI)

SECTION 8: Exposure controls/personal protection

Recommended monitoring procedures	: Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
-----------------------------------	--

DNELs/DMELs

Product/ingredient name	Туре	Exposure	Value	Population	Effects
methanol	DNEL	Short term Dermal	8 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	8 mg/kg bw/day	General population	Systemic
	DNEL	Short term Dermal	40 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Dermal	40 mg/kg bw/day	Workers	Systemic
	DNEL	Short term Inhalation	50 mg/m ³	General population	Local
	DNEL	Long term Inhalation	50 mg/m³	General population	Local
	DNEL	Short term Inhalation	50 mg/m³	General population	Systemic
	DNEL	Long term Inhalation	50 mg/m³	General	Systemic
	DNEL	Short term Inhalation	260 mg/m³	Workers	Local
	DNEL	Long term Inhalation	260 mg/m³	Workers	Local
	DNEL	Short term Inhalation	260 mg/m³	Workers	Systemic
	DNEL	Long term Inhalation	260 mg/m ³	Workers	Systemic
titanium dioxide	DNEL	Long term Inhalation	10 mg/m³	Workers	Local
	DNEL	Long term Oral	700 mg/kg bw/day	General population	Systemic

PNECs

No PNECs available

8.2 Exposure controls							
Appropriate engineering controls	:	ventilation	vith adequate ventilation or other engineering co nts below any recommo	ontrols to keep worker	exposure to air		
Individual protection meas	ures						
Hygiene measures	:	before eati Appropriate Contamina contamina	ds, forearms and face t ng, smoking and using e techniques should be ited work clothing shou ted clothing before reus re close to the workstat	the lavatory and at the used to remove poter Id not be allowed out o sing. Ensure that eyew	e end of the wor ntially contamina of the workplace	king pe ated clo . Was	eriod. othing. h
Eye/face protection	:	assessmer gases or d	wear complying with ar nt indicates this is nece usts. If contact is poss assessment indicates s.	essary to avoid exposu ible, the following prot	re to liquid spla: ection should be	shes, n e worn,	nists, ,
Date of issue/Date of revision		: 2/14/2023	Date of previous issue	: 2/14/2023	Version	: 23	8/17

Chemask® (UFI)

SECTION 8: Exposure controls/personal protection

Skin protection	
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Body protection	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

<u>Appearance</u>	
Physical state	: Liquid.
Colour	: Opaque. Pink [Light]
Odour	: Ammoniacal. [Slight]
Odour threshold	: Not available.
Melting point/freezing point	: Not available.
Initial boiling point and boiling range	: 38°C (100.4°F)
Flammability	: Not available.
Lower and upper explosion limit	: Not available.
Flash point	: [Product does not su

: [Product does not sustain combustion.]

	Closed cup			Open cup		
Ingredient name	°C	°F	Method	°C	°F	Method
methanol	9.7	49.5	Abel-Pensky			
1,2-Dihydro- 2,2,4-trimethylquinoline, oligomers	180	356				

Auto-ignition temperature

Ingredient name	°C	°F	Method	
sodium acrylate	438	820.4		
methanol	455	851	DIN 51794	
Decomposition temperature : Not available.				

Decomposition temperature pН

: Not available.

ŝ

Viscosity

- : Dynamic: 20000 mPa·s

Date of issue/Date of revision

Chemask® (UFI)

SECTION 9: Physical and chemical properties

•	• •
Solubility in water	: Not available.
Partition coefficient: n-octanol/ water	: Not applicable.
Vapour pressure	: 101.3 kPa (760 mm Hg)
Relative density	: Not available.
Density	: 0.9 g/cm ³
Vapour density	: <1 [Air = 1]
Particle characteristics	
Median particle size	: Not applicable.
9.2 Other information	
9.2.1 Information with regard to	physical hazard classes
Explosive properties	: Not applicable
Oxidising properties	: Not available.
9.2.2 Other safety characteristi	cs

SECTION 10: Stability and reactivity

10.1 Reactivity	:	No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	;	The product is stable.
10.3 Possibility of hazardous reactions	:	Under normal conditions of storage and use, hazardous reactions will not occur.
10.4 Conditions to avoid	:	No specific data.
10.5 Incompatible materials	:	No specific data.
10.6 Hazardous decomposition products	:	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Not available.

: >1 (butyl acetate = 1)

Acute toxicity

Miscible with water

Evaporation rate

Product/ingredient name	Result	Species	Dose	Exposure
zinc bis (dibutyldithiocarbamate)	LD50 Oral	Rat	>5000 mg/kg	-
methanol	LC50 Inhalation Gas. LC50 Inhalation Gas.	Rat Rat	145000 ppm 64000 ppm	1 hours 4 hours
	LD50 Dermal	Rabbit	15800 mg/kg	-
	LD50 Oral	Rat	5600 mg/kg	-
ammonia	LD50 Oral	Rat	350 mg/kg	-

Acute toxicity estimates

Chemask® (UFI)

SECTION 11: Toxicological information

U						1
Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)	
methanol ammonia	100 350	300 N/A	64000 N/A	3 N/A	N/A N/A	

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
zinc bis (dibutyldithiocarbamate)	Eyes - Mild irritant	Rabbit	-	39 milligrams	-
, <u>,</u> ,	Skin - Mild irritant	Rabbit	-	0.5 Grams	-
methanol	Eyes - Moderate irritant	Rabbit	-	24 hours 100 mg	-
	Eyes - Moderate irritant	Rabbit	-	40 mg	-
	Skin - Moderate irritant	Rabbit	-	24 hours 20 mg	-
titanium dioxide	Skin - Mild irritant	Human	-	72 hours 300 ug l	-
ammonia	Eyes - Severe irritant	Rabbit	-	0.5 minutes 1 mg	-
	Eyes - Severe irritant	Rabbit	-	250 ug	-
Conclusion/Summary	: Not available.				
<u>Sensitisation</u>					
Conclusion/Summary	: Not available.				
<u>Mutagenicity</u>					
Conclusion/Summary	: Not available.				
Carcinogenicity					
Conclusion/Summary	: Not available.				
Reproductive toxicity					

Conclusion/Summary : Not available.

Teratogenicity

Conclusion/Summary : Not available.

Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
zinc bis(dibutyldithiocarbamate)	Category 3	-	Respiratory tract irritation
methanol	Category 1	-	-
ammonia	Category 3	-	Respiratory tract irritation

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

Information on likely routes : Not available.

of exposure

Potential acute health effects

Eye contact : May cause eye irritation.

: Toxic if inhaled. Inhalation

Skin contact : Toxic in contact with skin. May cause an allergic skin reaction.

Date of issue/Date of revision

: 2/14/2023

Date of previous issue

Chemask® (UFI)

SECTION 11:	Toxicological	information
-------------	---------------	-------------

Ing	est	ion
-----	-----	-----

: Toxic if swallowed.

Symptoms related to the phy	sical, chemical and toxicological characteristics	
Eye contact	: Adverse symptoms may include the following: irritation redness watering	
Inhalation	: Adverse symptoms may include the following: headache dizziness/vertigo drowsiness/fatigue	
Skin contact	: Adverse symptoms may include the following: irritation redness	
Ingestion	: Adverse symptoms may include the following: Ingestion Seek medical attention.	

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Delayeu anu inineulate eneu	as well as chronic effects from short and long-term exposure	
Short term exposure		
Potential immediate effects	Not available.	
Potential delayed effects	Not available.	
Long term exposure		
Potential immediate effects	Not available.	
Potential delayed effects	Not available.	
Potential chronic health effe	<u>></u>	
Not available.		
Conclusion/Summary	Not available.	
General	Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.	t
Carcinogenicity	No known significant effects or critical hazards.	
Mutagenicity	No known significant effects or critical hazards.	
Reproductive toxicity	No known significant effects or critical hazards.	

11.2 Information on other hazards

11.2.1 Endocrine disrupting propertiesNot available.11.2.2 Other informationNot available.

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
methanol	Acute EC50 16.912 mg/l Marine water	Algae - Ulva pertusa	96 hours
	Acute LC50 2500000 µg/l Marine water	Crustaceans - Crangon crangon - Adult	48 hours
	Acute LC50 3289 mg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
	Acute LC50 290 mg/l Fresh water	Fish - Danio rerio - Egg	96 hours
	Chronic NOEC 9.96 mg/l Marine water	Algae - Ulva pertusa	96 hours
titanium dioxide	Acute LC50 3 mg/l Fresh water	Crustaceans - Ceriodaphnia dubia - Neonate	48 hours
ate of issue/Date of revision	: 2/14/2023 Date of previous issue	: 2/14/2023 Version	:23 12/

Chemask® (UFI)

SECTION 12: Ecological information

	Acute LC50 6.5 mg/l Fresh water	Daphnia - Daphnia pulex - Neonate	48 hours
	Acute LC50 >1000000 μg/l Marine water	Fish - Fundulus heteroclitus	96 hours
ammonia	Acute LC50 37 ppm Fresh water	Fish - Gambusia affinis - Adult	96 hours
Conclusion/Summary	: Not available.	·	

12.2 Persistence and degradability

Conclusion/Summary : Not available.

12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
methanol titanium dioxide	-0.77	<10 352	low low
		002	1011

12.4 N	<i>lobility</i>	in soil
--------	-----------------	---------

Soil/water partition coefficient (Koc)	: Not available.
Mobility	: Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Endocrine disrupting properties

Not available.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product	
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
Hazardous waste	: The classification of the product may meet the criteria for a hazardous waste.
Packaging	
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.
Special precautions	: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

Chemask® (UFI)

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	ΙΑΤΑ
14.1 UN number or ID number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name				
14.3 Transport hazard class(es)				
14.4 Packing group				
14.5 Environmental hazards	No.	No.	No.	No.

Additional information

ΙΑΤΑ

: The environmentally hazardous substance mark may appear if required by other transportation regulations.

14/17

14.6 Special precautions for user: **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Maritime transport in : Not available. **bulk according to IMO**

instruments

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH) Annex XIV - List of substances subject to authorisation **Annex XIV** None of the components are listed. Substances of very high concern None of the components are listed. Annex XVII - Restrictions : Not applicable. on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles Other EU regulations **Industrial emissions** : Not listed (integrated pollution prevention and control) -Air **Industrial emissions** : Not listed (integrated pollution prevention and control) -Water Ozone depleting substances (1005/2009/EU) Not listed. Date of issue/Date of revision : 2/14/2023 : 2/14/2023 Date of previous issue Version :23

Chemask® (UFI)

SECTION 15: Regulatory information

Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

Seveso Directive

This product is controlled under the Seveso Directive.

Danger criteria

Category

H2 E2

National regulations

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

Inventory list

inventory not		
Australia	:	All components are listed or exempted.
Canada	:	At least one component is not listed in DSL but all such components are listed in NDSL.
China	:	All components are listed or exempted.
Eurasian Economic Union	:	Russian Federation inventory: Not determined.
Japan	:	Japan inventory (CSCL): All components are listed or exempted. Japan inventory (ISHL): Not determined.
New Zealand	;	All components are listed or exempted.
Philippines	;	All components are listed or exempted.
Republic of Korea	:	All components are listed or exempted.
Taiwan	:	Not determined.
Thailand	:	Not determined.
Turkey	:	Not determined.
United States	:	Not determined.
Viet Nam	;	Not determined.
15.2 Chemical safety assessment	:	This product contains substances for which Chemical Safety Assessments are still required.

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Chemask® (UFI)

SECTION 16: Other information

Abbreviations and	: ATE = Acute Toxicity Estimate
acronyms	CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No.
	1272/2008]
	DMEL = Derived Minimal Effect Level
	DNEL = Derived No Effect Level
	EUH statement = CLP-specific Hazard statement
	N/A = Not available
	PBT = Persistent, Bioaccumulative and Toxic
	PNEC = Predicted No Effect Concentration
	RRN = REACH Registration Number
	SGG = Segregation Group
	vPvB = Very Persistent and Very Bioaccumulative
— • • • • • •	

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Acute Tox. 3, H301	Calculation method
Acute Tox. 3, H311	Calculation method
Acute Tox. 3, H331	Calculation method
Skin Sens. 1, H317	Calculation method
Aquatic Chronic 2, H411	Calculation method

Full text of abbreviated H statements

H225	Highly flammable liquid and vapour.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H335	May cause respiratory irritation.
H351	Suspected of causing cancer.
H370	Causes damage to organs.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Full text of classifications [CLP/GHS]

CUTE TOXICITY - Category 3			
DNG-TERM (CHRONIC) AQUATIC HAZARD - Category 2			
DNG-TERM (CHRONIC) AQUATIC HAZARD - Category 3			
ARCINOGENICITY - Category 2			
ERIOUS EYE DAMAGE/EYE IRRITATION - Category 2			
AMMABLE LIQUIDS - Category 2			
KIN CORROSION/IRRITATION - Category 1B			
KIN CORROSION/IRRITATION - Category 2			
KIN SENSITISATION - Category 1			
PECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 1			
PECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3			
: 2/14/2023			
: 2/14/2023			
: 2/14/2023			
: 23			
: 2/14/2023 Date of previous issue : 2/14/2023 Version	on :2	23 1	16/17
	CUTE TOXICITY - Category 4 HORT-TERM (ACUTE) AQUATIC HAZARD - Category 1 DNG-TERM (CHRONIC) AQUATIC HAZARD - Category 2 DNG-TERM (CHRONIC) AQUATIC HAZARD - Category 2 DNG-TERM (CHRONIC) AQUATIC HAZARD - Category 3 ARCINOGENICITY - Category 2 ERIOUS EYE DAMAGE/EYE IRRITATION - Category 2 AMMABLE LIQUIDS - Category 2 (IN CORROSION/IRRITATION - Category 1B (IN CORROSION/IRRITATION - Category 1 PECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 1 PECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3 : 2/14/2023 : 2/14/2023 : 2/14/2023 : 23	CUTE TOXICITY - Category 4 HORT-TERM (ACUTE) AQUATIC HAZARD - Category 1 DNG-TERM (CHRONIC) AQUATIC HAZARD - Category 2 DNG-TERM (CHRONIC) AQUATIC HAZARD - Category 2 DNG-TERM (CHRONIC) AQUATIC HAZARD - Category 3 ARCINOGENICITY - Category 2 ERIOUS EYE DAMAGE/EYE IRRITATION - Category 2 AMMABLE LIQUIDS - Category 2 (IN CORROSION/IRRITATION - Category 1B (IN CORROSION/IRRITATION - Category 2 (IN SENSITISATION - Category 1 PECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 1 PECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3 : 2/14/2023 : 2/14/2023 : 2/14/2023 : 23	CUTE TOXICITY - Category 4 HORT-TERM (ACUTE) AQUATIC HAZARD - Category 1 DNG-TERM (CHRONIC) AQUATIC HAZARD - Category 1 DNG-TERM (CHRONIC) AQUATIC HAZARD - Category 2 DNG-TERM (CHRONIC) AQUATIC HAZARD - Category 3 ARCINOGENICITY - Category 2 ERIOUS EYE DAMAGE/EYE IRRITATION - Category 2 AMMABLE LIQUIDS - Category 2 (IN CORROSION/IRRITATION - Category 1B (IN CORROSION/IRRITATION - Category 2 CIN SENSITISATION - Category 1 PECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 1 PECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3 : 2/14/2023 : 2/14/2023 : 2/14/2023 : 23

Chemask® (UFI)

SECTION 16: Other information

To the best of our knowledge, the information contained herein is accurate. However, neither the abovenamed supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.