

SAFETY DATA SHEET



Flux-Off®Rosin (UK - Great Britain)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : Flux-Off®Rosin (UK - Great Britain)
Product code : ES835BE
Product description : Remover.
Product type : Aerosol.
Other means of identification : Processing aid Fluxing agents Remover.
Industrial/Professional use
UFI: WXA8-C0HT-A00A-VCMB

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses	
Processing aid Flux agent Remover. Product Application and Material uses Reference Website: or Label QR code	
Uses advised against	Reason
Other	Industrial/Professional use

1.3 Details of the supplier of the safety data sheet

Manufacturer
Chemtronics
8125 Cobb Center Drive
Kennesaw, GA 30152
Tel. 770-424-4888 or toll free 800-645-5244

Distributor

Importer
Rocol, a division of ITW Limited
Wakefield Road, Swillington
Leeds, West Yorkshire, LS26 8BS
United Kingdom
Tel: +44 (0) 113 232 2600

e-mail address of person responsible for this SDS : Only Representative (UK)
Rocol, a division of ITW Limited
Wakefield Road, Swillington
Leeds, West Yorkshire, LS26 8BS
United Kingdom
Tel: +44 (0) 113 232 2600

National contact

Rocol, a division of ITW Limited
Wakefield Road, Swillington
Leeds, West Yorkshire, LS26 8BS
United Kingdom
Tel: +44 (0) 113 232 2600

1.4 Emergency telephone number

National advisory body/Poison Centre

SECTION 1: Identification of the substance/mixture and of the company/undertaking

Telephone number	: EMERGENCY HEALTH INFORMATION: United Kingdom (England or Wales) 0845 46 47 or Scotland 08454 24 24 24 (UK only).
Supplier	
Telephone number	: Chemtronics Product Information: 800-TECH-401 (800-832-4401) Chemtronics Customer Service: 800-645-5244
Hours of operation	: 8:00AM to 5:00 PM
Information limitations	: EMERGENCY HEALTH INFORMATION: EMERGENCY SPILL INFORMATION: Transport information

SECTION 2: Hazards identification**2.1 Classification of the substance or mixture**

Product definition : Mixture

Classification according to UK CLP/GHS

Aerosol 1, H222, H229

Skin Irrit. 2, H315

Eye Irrit. 2, H319

STOT SE 3, H336

Aquatic Chronic 2, H411

The product is classified as hazardous according to UK CLP Regulation SI 2019/720 as amended.

Ingredients of unknown toxicity : 91 percent of the mixture consists of component(s) of unknown acute oral toxicity
100 percent of the mixture consists of component(s) of unknown acute dermal toxicity
84 percent of the mixture consists of component(s) of unknown acute inhalation toxicity

Ingredients of unknown ecotoxicity : Contains 25% of components with unknown hazards to the aquatic environment

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms :



Signal word : Danger

Hazard statements : Extremely flammable aerosol. Pressurised container: may burst if heated.
Causes skin irritation.
Causes serious eye irritation.
May cause drowsiness or dizziness.
Toxic to aquatic life with long lasting effects.

Precautionary statements

Prevention	: Wear protective gloves. Wear eye or face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Avoid release to the environment. Avoid breathing dust or mist. Wash thoroughly after handling. Do not pierce or burn, even after use.
Response	: Collect spillage. IF INHALED: Call a POISON CENTER or doctor if you feel unwell. IF ON SKIN: Wash with plenty of water. Take off contaminated clothing and wash it before reuse. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.
Storage	: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Store in a well-ventilated place. Keep container tightly closed.

SECTION 2: Hazards identification

- Disposal** : Dispose of contents and container in accordance with all local, regional, national and international regulations.
- Supplemental label elements** : FOR INDUSTRIAL USE ONLY
For professional use only.
- Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles** : Not applicable.
- Special packaging requirements**
- Containers to be fitted with child-resistant fastenings** : Not applicable.
- Tactile warning of danger** : Not applicable.

2.3 Other hazards

- Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII** : This mixture does not contain any substances that are assessed to be a PBT or a vPvB.
- Other hazards which do not result in classification** : None known.

SECTION 3: Composition/information on ingredients**3.2 Mixtures** : Mixture

Product/ingredient name	Identifiers	%	Classification	Type
2-methylpentane	EC: 203-523-4 CAS: 107-83-5 Index: 601-007-00-7	≥25 - ≤50	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411	[1]
3-methylpentane	EC: 202-481-4 CAS: 96-14-0 Index: 601-007-00-7	≥10 - ≤25	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411	[1]
ethanol	EC: 200-578-6 CAS: 64-17-5 Index: 603-002-00-5	≥10 - ≤25	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Aquatic Chronic 2, H411	[1] [2]
2,2-dimethylbutane	EC: 200-906-8 CAS: 75-83-2 Index: 601-007-00-7	≤10	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411	[1]
2,3-dimethylbutane	EC: 201-193-6 CAS: 79-29-8 Index: 601-007-00-7	≤10	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411	[1]
propan-2-ol	EC: 200-661-7 CAS: 67-63-0 Index: 603-117-00-0	≤10	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336	[1] [2]

SECTION 3: Composition/information on ingredients

n-hexane	EC: 203-777-6 CAS: 110-54-3 Index: 601-037-00-0	<1	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Repr. 2, H361f STOT SE 3, H336 STOT RE 1, H372 (nervous system) Asp. Tox. 1, H304 Aquatic Chronic 2, H411	[1] [2]
propyl acetate	EC: 203-686-1 CAS: 109-60-4 Index: 607-024-00-6	<1	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336 Aquatic Chronic 3, H412 EUH066	[1] [2]

Type

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

See Section 16 for the full text of the H statements declared above.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures**4.1 Description of first aid measures**

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Skin contact** : Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. If necessary, call a poison center or physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

4.2 Most important symptoms and effects, both acute and delayedOver-exposure signs/symptoms

SECTION 4: First aid measures

- Eye contact** : Adverse symptoms may include the following:
pain or irritation
watering
redness
- Inhalation** : Adverse symptoms may include the following:
respiratory tract irritation
coughing
nausea or vomiting
headache
drowsiness/fatigue
dizziness/vertigo
unconsciousness
- Skin contact** : Adverse symptoms may include the following:
irritation
redness
- Ingestion** : Adverse symptoms may include the following:
Ingestion Seek medical attention.

4.3 Indication of any immediate medical attention and special treatment needed

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media** : Use an extinguishing agent suitable for the surrounding fire.
- Unsuitable extinguishing media** : None known.

5.2 Special hazards arising from the substance or mixture

- Hazards from the substance or mixture** : Extremely flammable aerosol. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Gas may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back, causing fire or explosion. Bursting aerosol containers may be propelled from a fire at high speed. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
- Hazardous combustion products** : Decomposition products may include the following materials:
carbon dioxide
carbon monoxide

5.3 Advice for firefighters

- Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to British standard BS EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. In the case of aerosols being ruptured, care should be taken due to the rapid escape of the pressurised contents and propellant. If a large number of containers are ruptured, treat as a bulk material spillage according to the instructions in the clean-up section. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing dust or mist. Put on appropriate personal protective equipment.
- For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

- : Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

6.3 Methods and material for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

6.4 Reference to other sections

- : See Section 1 for emergency contact information.
See Section 8 for information on appropriate personal protective equipment.
See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Pressurised container: protect from sunlight and do not expose to temperature exceeding 50°C. Do not pierce or burn, even after use. Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing gas. Avoid breathing vapour or mist. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Empty containers retain product residue and can be hazardous.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

SECTION 7: Handling and storage

Store in accordance with local regulations. Store away from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Seveso Directive - Reporting thresholds**Danger criteria**

Category	Notification and MAPP threshold	Safety report threshold
P3a	150 tonnes	500 tonnes
E2	200 tonnes	500 tonnes

7.3 Specific end use(s)

Recommendations : Not available.

Industrial sector specific solutions : Not available.

SECTION 8: Exposure controls/personal protection**8.1 Control parameters****Occupational exposure limits**

Product/ingredient name	Exposure limit values
ethanol	EH40/2005 WELs (United Kingdom (UK), 1/2020) TWA 8 hours: 1000 ppm. TWA 8 hours: 1920 mg/m ³ .
propan-2-ol	EH40/2005 WELs (United Kingdom (UK), 1/2020) STEL 15 minutes: 1250 mg/m ³ . STEL 15 minutes: 500 ppm. TWA 8 hours: 999 mg/m ³ . TWA 8 hours: 400 ppm.
n-hexane	EH40/2005 WELs (United Kingdom (UK), 1/2020) TWA 8 hours: 72 mg/m ³ . TWA 8 hours: 20 ppm.
propyl acetate	EH40/2005 WELs (United Kingdom (UK), 1/2020) STEL 15 minutes: 1060 mg/m ³ . STEL 15 minutes: 250 ppm. TWA 8 hours: 849 mg/m ³ . TWA 8 hours: 200 ppm.

Biological exposure indices

No exposure indices known.

Recommended monitoring procedures : Reference should be made to monitoring standards, such as the following: British Standard BS EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) British Standard BS EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) British Standard BS EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

Product/ingredient name	Result
-------------------------	--------

SECTION 8: Exposure controls/personal protection

ethanol

DNEL - Workers - Long term - Inhalation380 mg/m³Effects: Systemic**DNEL - General population - Long term - Oral**

87 mg/kg bw/day

Effects: Systemic**DNEL - General population - Long term - Inhalation**114 mg/m³Effects: Systemic**DNEL - General population - Long term - Dermal**

206 mg/kg bw/day

Effects: Systemic**DNEL - Workers - Long term - Dermal**

343 mg/kg bw/day

Effects: Systemic**DNEL - General population - Short term - Inhalation**950 mg/m³Effects: Local**DNEL - Workers - Short term - Inhalation**1900 mg/m³Effects: Local

2,2-dimethylbutane

DNEL - General population - Long term - Inhalation1131 mg/m³Effects: Systemic**DNEL - General population - Long term - Oral**

1301 mg/kg bw/day

Effects: Systemic**DNEL - General population - Long term - Dermal**

1377 mg/kg bw/day

Effects: Systemic**DNEL - Workers - Long term - Inhalation**5306 mg/m³Effects: Systemic**DNEL - Workers - Long term - Dermal**

13964 mg/kg bw/day

Effects: Systemic

2,3-dimethylbutane

DNEL - General population - Long term - Inhalation1131 mg/m³Effects: Systemic**DNEL - General population - Long term - Oral**

1301 mg/kg bw/day

Effects: Systemic**DNEL - General population - Long term - Dermal**

1377 mg/kg bw/day

Effects: Systemic**DNEL - Workers - Long term - Inhalation**5306 mg/m³Effects: Systemic

SECTION 8: Exposure controls/personal protection

propan-2-ol

DNEL - Workers - Long term - Dermal

13964 mg/kg bw/day

Effects: Systemic**DNEL - Workers - Long term - Inhalation**500 mg/m³Effects: Systemic**DNEL - Workers - Long term - Dermal**

888 mg/kg bw/day

Effects: Systemic**DNEL - General population - Long term - Oral**

26 mg/kg bw/day

Effects: Systemic**DNEL - General population - Short term - Oral**

51 mg/kg bw/day

Effects: Systemic**DNEL - General population - Long term - Inhalation**89 mg/m³Effects: Systemic**DNEL - General population - Short term - Inhalation**178 mg/m³Effects: Systemic**DNEL - General population - Long term - Dermal**

319 mg/kg bw/day

Effects: Systemic**DNEL - Workers - Short term - Inhalation**1000 mg/m³Effects: Systemic

n-hexane

DNEL - General population - Long term - Oral

4 mg/kg bw/day

Effects: Systemic**DNEL - General population - Long term - Dermal**

5.3 mg/kg bw/day

Effects: Systemic**DNEL - Workers - Long term - Dermal**

11 mg/kg bw/day

Effects: Systemic**DNEL - General population - Long term - Inhalation**16 mg/m³Effects: Systemic**DNEL - Workers - Long term - Inhalation**75 mg/m³Effects: Systemic

propyl acetate

DNEL - General population - Long term - Inhalation149 mg/m³Effects: Systemic**DNEL - General population - Long term - Inhalation**210 mg/m³Effects: Local

SECTION 8: Exposure controls/personal protection

DNEL - General population - Short term - Inhalation

298 mg/m³

Effects: Systemic

DNEL - General population - Short term - Inhalation

420 mg/m³

Effects: Local

DNEL - Workers - Long term - Inhalation

420 mg/m³

Effects: Local

DNEL - Workers - Short term - Inhalation

840 mg/m³

Effects: Local

PNECs

Not available.

8.2 Exposure controls

Appropriate engineering controls

- : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Individual protection measures

Hygiene measures

- : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

- : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

Skin protection

Hand protection

- : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Body protection

- : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves. Refer to British Standard BS EN 1149 for further information on material and design requirements and test methods.

Other skin protection

- : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

- : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

SECTION 8: Exposure controls/personal protection

Environmental exposure controls : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Appearance

Physical state : Liquid. [Aerosol.]
Colour : Not available.
Odour : Hydrocarbon. Characteristic. [Slight]
Odour threshold : Not available.
Melting point/freezing point : Not available.
Initial boiling point and boiling range : Not available.
Flammability (solid, gas) : Not available.
Upper/lower flammability or explosive limits : Not available.
Flash point : Closed cup: -29°C (-20.2°F)
Auto-ignition temperature : Not available.
Decomposition temperature : Not available.
pH : Not available.
Viscosity : Dynamic (room temperature): Not available.
Kinematic (room temperature): Not available.
Kinematic (40°C): Not available.
Solubility in water : Not available.
Partition coefficient: n-octanol/ water : Not applicable.
Vapour pressure :

Ingredient name	Vapour Pressure at 20°C			Vapour pressure at 50°C		
	mm Hg	kPa	Method	mm Hg	kPa	Method
propane	6300.51192	840				
isobutane	2280.18527	304				
2-methylpentane	172.51402	23				
3-methylpentane	153.76249	20.5				
n-hexane	127.51036	17				
ethanol	42.94865	5.7				
propyl acetate	35.92805	4.8				
propan-2-ol	33.00268	4.4				

Evaporation rate : >1 (butyl acetate = 1)
Relative density : Not available.
Vapour density : Not available.
Explosive properties : Not applicable
Oxidising properties : Not applicable
Particle characteristics
Median particle size : Not applicable.

9.2 Other information

Flux-Off®Rosin (UK - Great Britain)

SECTION 9: Physical and chemical properties

Heat of combustion : 29.8 kJ/g
Aerosol product
Type of aerosol : Spray

SECTION 10: Stability and reactivity

10.1 Reactivity : No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability : The product is stable.
10.3 Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will not occur.
10.4 Conditions to avoid : Avoid all possible sources of ignition (spark or flame).
10.5 Incompatible materials : No specific data.
10.6 Hazardous decomposition products : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1 Information on toxicological effects
Acute toxicity
Product/ingredient name Result
ethanol Rat - Oral - LD50
7 g/kg
Toxic effects: Behavioral - Aggression
Rat - Inhalation - LC50 Vapour
124700 mg/m³ [4 hours]
propan-2-ol Rabbit - Dermal - LD50
12800 mg/kg
Rat - Oral - LD50
5000 mg/kg
Toxic effects: Behavioral - General anesthetic
n-hexane Rat - Oral - LD50
15840 mg/kg
Rat - Inhalation - LC50 Gas.
48000 ppm [4 hours]
propyl acetate Rat - Oral - LD50
9370 mg/kg
Toxic effects: Behavioral - Somnolence (general depressed activity) Other - Hair
Conclusion/Summary [Product] : Not available.
Acute toxicity estimates

SECTION 11: Toxicological information

Product/ingredient name	Oral (mg/kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
ethanol	7000	N/A	N/A	124.7	N/A
propan-2-ol	5000	12800	N/A	N/A	N/A
n-hexane	15840	N/A	48000	N/A	N/A
propyl acetate	9370	N/A	N/A	N/A	N/A

Skin corrosion/irritation**Product/ingredient name**

ethanol

Result**Rabbit - Skin - Mild irritant**Amount/concentration applied: 400 mg**Rabbit - Skin - Moderate irritant**Duration of treatment/exposure: 24 hoursAmount/concentration applied: 20 mg

propan-2-ol

Rabbit - Skin - Mild irritantAmount/concentration applied: 500 mg

propyl acetate

Rabbit - Skin - Mild irritantAmount/concentration applied: 500 mg**Conclusion/Summary [Product]** : Not available.**Serious eye damage/eye irritation****Product/ingredient name**

ethanol

Result**Rabbit - Eyes - Mild irritant**Duration of treatment/exposure: 24 hoursAmount/concentration applied: 500 mg**Rabbit - Eyes - Moderate irritant**Duration of treatment/exposure: 0.066666667 minutesAmount/concentration applied: 100 mg**Rabbit - Eyes - Moderate irritant**Amount/concentration applied: 100 uL**Rabbit - Eyes - Severe irritant**Amount/concentration applied: 500 mg**Rabbit - Eyes - Mild irritant**Duration of treatment/exposure: 1 hoursAmount/concentration applied: 50 pph

propan-2-ol

Rabbit - Eyes - Moderate irritantDuration of treatment/exposure: 24 hoursAmount/concentration applied: 100 mg**Rabbit - Eyes - Moderate irritant**Amount/concentration applied: 10 mg**Rabbit - Eyes - Severe irritant**Amount/concentration applied: 100 mg

n-hexane

Rabbit - Eyes - Mild irritantAmount/concentration applied: 10 mg

propyl acetate

Rabbit - Eyes - Mild irritantDuration of treatment/exposure: 24 hours

SECTION 11: Toxicological information

Amount/concentration applied: 500 mg

Conclusion/Summary [Product] : Not available.

Respiratory corrosion/irritation

Not available.

Conclusion/Summary [Product] : Not available.

Respiratory or skin sensitization

Not available.

Skin

Conclusion/Summary [Product] : Not available.

Respiratory

Conclusion/Summary [Product] : Not available.

Germ cell mutagenicity

Not available.

Conclusion/Summary [Product] : Not available.

Carcinogenicity

Not available.

Conclusion/Summary [Product] : Not available.

Reproductive toxicity

Not available.

Conclusion/Summary [Product] : Not available.

Specific target organ toxicity (single exposure)

Product/ingredient name	Result
2-methylpentane	STOT SE 3, H336 (Narcotic effects)
3-methylpentane	STOT SE 3, H336 (Narcotic effects)
2,2-dimethylbutane	STOT SE 3, H336 (Narcotic effects)
2,3-dimethylbutane	STOT SE 3, H336 (Narcotic effects)
propan-2-ol	STOT SE 3, H336 (Narcotic effects)
n-hexane	STOT SE 3, H336 (Narcotic effects)
propyl acetate	STOT SE 3, H336 (Narcotic effects)

Specific target organ toxicity (repeated exposure)

Product/ingredient name	Result
n-hexane	STOT RE 1, H372 (nervous system)

Aspiration hazard

Product/ingredient name	Result
-------------------------	--------

SECTION 11: Toxicological information

2-methylpentane	ASPIRATION HAZARD - Category 1
3-methylpentane	ASPIRATION HAZARD - Category 1
2,2-dimethylbutane	ASPIRATION HAZARD - Category 1
2,3-dimethylbutane	ASPIRATION HAZARD - Category 1
n-hexane	ASPIRATION HAZARD - Category 1

Information on likely routes of exposure

Not available.

Potential acute health effects

Eye contact	: Causes serious eye irritation.
Inhalation	: Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness.
Skin contact	: Causes skin irritation.
Ingestion	: Can cause central nervous system (CNS) depression.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact	: Adverse symptoms may include the following: pain or irritation watering redness
Inhalation	: Adverse symptoms may include the following: respiratory tract irritation coughing nausea or vomiting headache drowsiness/fatigue dizziness/vertigo unconsciousness
Skin contact	: Adverse symptoms may include the following: irritation redness
Ingestion	: Adverse symptoms may include the following: Ingestion Seek medical attention.

Delayed and immediate effects as well as chronic effects from short and long-term exposure**Short term exposure**

Potential immediate effects	: Not available.
Potential delayed effects	: Not available.

Long term exposure

Potential immediate effects	: Not available.
Potential delayed effects	: Not available.

Potential chronic health effects

Not available.

Conclusion/Summary [Product] : Not available.

General	: No known significant effects or critical hazards.
Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.
Reproductive toxicity	: No known significant effects or critical hazards.

Other information

Not available.

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name	Result
ethanol	Acute - LC50 - Fresh water Fish - Rainbow trout,donaldson trout - <i>Oncorhynchus mykiss</i> 42 mg/l [4 days] <u>Effect</u>: Mortality Acute - EC50 - Marine water Algae - Green algae - <i>Ulva pertusa</i> 17.921 mg/l [96 hours] <u>Effect</u>: Reproduction Chronic - NOEC - Marine water Algae - Green algae - <i>Ulva pertusa</i> 4.995 mg/l [96 hours] <u>Effect</u>: Reproduction Chronic - NOEC - Fresh water Fish - Eastern mosquitofish - <i>Gambusia holbrooki</i> - Larvae <u>Age</u>: 3 days 0.375 µl/l [12 weeks] <u>Effect</u>: Morphology Chronic - NOEC - Fresh water Daphnia - Water flea - <i>Daphnia magna</i> - Neonate <u>Age</u>: <24 hours 100 µl/l [21 days] <u>Effect</u>: Mortality Acute - EC50 - Fresh water Daphnia - Water flea - <i>Daphnia magna</i> 2 mg/l [48 hours] <u>Effect</u>: Intoxication
propan-2-ol	Acute - LC50 - Marine water Crustaceans - Common shrimp, sand shrimp - <i>Crangon crangon</i> 1400 mg/l [48 hours] <u>Effect</u>: Mortality Acute - LC50 - Fresh water Fish - Harlequinfish, red rasbora - <i>Rasbora heteromorpha</i> <u>Size</u>: 1 to 3 cm 4200 mg/l [96 hours] <u>Effect</u>: Mortality
n-hexane	Acute - LC50 - Fresh water Fish - Fathead minnow - <i>Pimephales promelas</i> <u>Age</u>: 31 days; <u>Size</u>: 20.4 mm; <u>Weight</u>: 0.123 g 2500 µg/l [96 hours] <u>Effect</u>: Mortality
propyl acetate	Acute - LC50 - Fresh water Fish - Fathead minnow - <i>Pimephales promelas</i> <u>Age</u>: 30 days; <u>Size</u>: 20.4 mm; <u>Weight</u>: 0.148 g 60 mg/l [96 hours] <u>Effect</u>: Mortality

Conclusion/Summary [Product] : Not available.

12.2 Persistence and degradability

SECTION 12: Ecological information

Not available.

Conclusion/Summary [Product] : Not available.**12.3 Bioaccumulative potential**

Product/ingredient name	LogP _{ow}	BCF	Potential
3-methylpentane	3.6	-	Low
ethanol	-0.35	-	Low
2,2-dimethylbutane	3.82	-	Low
2,3-dimethylbutane	3.42	-	Low
propan-2-ol	0.05	-	Low
n-hexane	4	501.187	High
propyl acetate	1.4	-	Low

12.4 Mobility in soil**Soil/water partition coefficient** : Not available.**Mobility** : Not available.**12.5 Results of PBT and vPvB assessment**

Product/ingredient name	PBT	P	B	T	vPvB	vP	vB
2-methylpentane	No	N/A	N/A	No	N/A	N/A	N/A
3-methylpentane	No	N/A	N/A	No	N/A	N/A	N/A
ethanol	No	N/A	N/A	No	N/A	N/A	N/A
2,2-dimethylbutane	No	N/A	N/A	No	N/A	N/A	N/A
2,3-dimethylbutane	No	N/A	N/A	No	N/A	N/A	N/A
propan-2-ol	No	N/A	N/A	No	N/A	N/A	N/A
n-hexane	No	N/A	No	Yes	No	N/A	No
propyl acetate	No	N/A	N/A	No	N/A	N/A	N/A

12.6 Other adverse effects : No known significant effects or critical hazards.**SECTION 13: Disposal considerations**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods**Product**

Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Hazardous waste : The classification of the product may meet the criteria for a hazardous waste.

Packaging

Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

SECTION 13: Disposal considerations

Special precautions : This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Do not puncture or incinerate container.

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA
14.1 UN number	UN1950	UN1950	UN1950	UN1950
14.2 UN proper shipping name	Aerosols, flammable	Aerosols, flammable	AEROSOLS Limited quantity	Aerosols, flammable
14.3 Transport hazard class(es)	2.1 	2.1 	2.1 	2.1 
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No	No	No.	No.

Additional information

ADR/RID : The environmentally hazardous substance mark is not required when transported in sizes of ≤5 L or ≤5 kg.
Tunnel code (D)

ADN : The environmentally hazardous substance mark is not required when transported in sizes of ≤5 L or ≤5 kg.

IATA : The environmentally hazardous substance mark may appear if required by other transportation regulations.

14.6 Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Transport in bulk according to IMO instruments : Not available.

SECTION 15: Regulatory information**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
UK (GB)/REACH**Annex XIV - List of substances subject to authorisation****Annex XIV**

None of the components are listed above the relevant limit.

Substances of very high concern

None of the components are listed above the relevant limit.

Ozone depleting substances

Not listed.

Prior Informed Consent (PIC)

Not listed.

Persistent Organic Pollutants

SECTION 15: Regulatory information

Not listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

No listed substance

Aerosol dispensers

:

**UK
CA**



Extremely flammable

Seveso Directive

This product is controlled under the Seveso Directive.

Danger criteria

Category

P3a
E2

EU regulations

**Industrial emissions
(integrated pollution
prevention and control) -
Air** : Not listed

**Industrial emissions
(integrated pollution
prevention and control) -
Water** : Not listed

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

Inventory list

Australia : All components are listed or exempted.
Canada : All components are listed or exempted.
Chile : Not determined.
China : All components are listed or exempted.
Colombia : Not determined.
Eurasian Economic Union : **Russian Federation inventory**: All components are listed or exempted.
Japan : **Japan inventory (CSCL)**: All components are listed or exempted.
Japan inventory (ISHL): All components are listed or exempted.

SECTION 15: Regulatory information

New Zealand	: All components are listed or exempted.
Philippines	: All components are listed or exempted.
Republic of Korea	: All components are listed or exempted.
Taiwan	: All components are listed or exempted.
Thailand	: All components are listed or exempted.
Turkey	: Not determined.
United States	: All components are active or exempted.
Viet Nam	: All components are listed or exempted.

15.2 Chemical safety assessment	: This product contains substances for which Chemical Safety Assessments are still required.
--	--

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and acronyms	ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road ATE = Acute Toxicity Estimate GB CLP = UK CLP (EC No 1272/2008) on the Classification, Labelling and Packaging of Substances and Mixtures as amended by (EU Exit) Regulations 2019 No. 720 and amendments DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level EUH statement = GB CLP-specific Hazard statement IATA = International Air Transport Association IMDG = International Maritime Dangerous Goods IMO = International Maritime Organization N/A = Not available PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail RRN = REACH Registration Number SGG = Segregation Group vPvB = Very Persistent and Very Bioaccumulative
-----------------------------------	---

Procedure used to derive the classification

Classification	Justification
Aerosol 1, H222, H229	On basis of test data
Skin Irrit. 2, H315	Calculation method
Eye Irrit. 2, H319	Calculation method
STOT SE 3, H336	Calculation method
Aquatic Chronic 2, H411	Calculation method

Full text of abbreviated H statements

H222, H229	Extremely flammable aerosol. Pressurised container: may burst if heated.
H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H361f	Suspected of damaging fertility.
H372	Causes damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

Full text of classifications

Flux-Off®Rosin (UK - Great Britain)

SECTION 16: Other information

Aerosol 1	AEROSOLS - Category 1
Aquatic Chronic 2	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2
Aquatic Chronic 3	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3
Asp. Tox. 1	ASPIRATION HAZARD - Category 1
Eye Irrit. 2	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2
Flam. Liq. 2	FLAMMABLE LIQUIDS - Category 2
Repr. 2	REPRODUCTIVE TOXICITY - Category 2
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
STOT RE 1	SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 1
STOT SE 3	SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3

Date of printing : 8/25/2026

Date of issue/ Date of revision : 8/25/2026

Date of previous issue : 8/25/2026

Version : 3

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.
Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.